200.1	REACTION MOTOR (E.G., MOTIVE	229	With plural selectively usable motive fluid ejecting means
	FLUID GENERATOR AND REACTION	230	Jet stream deflecting means
	NOZZLE, ETC.)		3
201	.Rotating or cyclic movement	231	By secondary fluid injection
	during axial thrust	232	Motive fluid outlet movable
202	.Ion motor		relative to motor part
203.1	.Electric, nuclear, or radiated energy fluid heating means	233	.Condition responsive thrust varying means
204		234	Solid propellant depletion
	.Method of operation	_01	control
205	By chemical reaction	235	Motive fluid outlet area and
206	Utilizing indirect heat	233	fuel flow control
	exchange	236	Plural spool motor-compressors
207	Utilizing plural reaction	237	Outlet area sensed to control
	zones within a system	237	fuel or oxidizer flow
208	Injecting air into the	220	
	reaction zone	238	Motive fluid temperature
209	Including using additive material		sensed to control fuel flow or outlet area
210	Injected separately	239	Compressor or turbine speed
211	Injected separatelyInjecting separate streams of		sensed to control fuel flow or
211	fuel and oxidizer (e.g.,		outlet area
	hypergole, etc.) into the	240	Oxidizer and fuel flow control
	reaction zone	241	Plural burners in series
212		242	Outlet area control
	Using igniter aid	243	Fuel flow control
213	Injected separately	244	.Motive fluid from diverse
214	Oxidizer in the form of a	211	generators alternatively
0.1 =	mixture		ejected through outlet
215	Fuel in the form of a mixture	245	Propellant supply used in one
216	One component free metal	243	operation reduced before
217	Injecting mixture of fuel and		starting another
	oxidizer into the reaction	246	.Turborocket
	zone	247	.Intermittent combustion
218	Decomposing a compound in the		
	reaction zone	248	Air bypass passage
219	Using solid material in	249	Aerodynamic valve
	reaction zone	250	.Plural propellants to burn
220	Including injecting modifying		sequentially
	fluid	251	.Solid and fluid propellant
221	.Motive fluid principally liquid	252	.Gel propellant
222	Plural discharge outlets	253	.Solid propellant
223	.With destruction sensing and	254	Including means to terminate or regulate motive fluid
224	preventing means		production
224	.Interrelated reaction motors	255	Including propellant support
225	Sequentially operated	233	means
226.1	Air and diverse fluid discharge	256	Including ignition means
	from separate discharge	257	Liquid oxidizer
006.0	outlets (e.g., fan jet, etc.)	257	Including injector means
226.2	Having thrust reverser		
226.3	Having means to effect a	259	Including pressurizing means
	variable bypass ratio	260	Including heating means
227	.Motive fluid principally steam	761	.Having afterburner
228	.With thrust direction modifying	762	Having oxidizer bypassed to
	means		afterburner feature

763	Movable flame holder	604	With heat exchanger to transfer
764	Fuel flow control		energy from engine exhaust to
765	Particular flame holder		motive fluid for motor
	structure	605.1	Supercharging means driven by
766	Particular liner or casing		engine exhaust actuated motor
	structure	605.2	With exhaust gas recirculation
262	.Air passage bypasses combustion	605.3	With motor bearing lubrication
	chamber		or cooling
263	.Plural motive fluid generating	606	With means to provide
	means or plural outlets		additional motive fluid for
264	.Including motive fluid treating		motor
	means	607	With additional drive means
265	.Means to flow film on surface		for supercharging means
266	.Including heat exchange means	608	With condition responsive
267	For a liquid		drive means control
268	.Including counter rotating	609	Fluid motor and engine each
	rotors		drive at least one means to
269	.Including mechanical air		supercharge the engine
	compressor or air flow	610	Supercharging means
	inducing means		convertible from series to
767	.Air supplied by ram effect		parallel
	(e.g., ramjet, etc.)	611	Having condition responsive
768	Supersonic speed therethrough		means to control supercharged
	(e.g., scramjet, etc.)		flow to engine
769	Solid fuel	612	Plural superchargers
770	.Particular exhaust nozzle	613	.With means to store combustion
	feature		products prior to entry into
771	Having variable area	C1.4	fluid motor means
595	INTERNAL COMBUSTION TYPE FREE	614	.Having fluid motor motive fluid
	PISTON DEVICE SUPPLIES MOTIVE		treating, controlling or
	FLUID TO MOTOR	615	conditioning means
596	INTERNAL COMBUSTION TYPE FREE	012	Having condition responsive control of motive fluid
	PISTON DEVICE WITH PRESSURE	C1 C	
	FLUID STARTING MEANS	616	Having means to transfer heat
597	FLUID MOTOR MEANS DRIVEN BY WASTE		<pre>energy between engine exhaust and motive fluid for fluid</pre>
	HEAT OR BY EXHAUST ENERGY FROM		motor
	INTERNAL COMBUSTION ENGINE	617	And having means to add fluid
598	.With supercharging means for	017	to motive fluid
	engine	618	Motive fluid is vaporized
599	With means to change	010	liquid
	temperature of supercharged	619	Having means to add a diverse
	flow	019	fluid to combustion products
600	With condition responsive valve	620	.Fluid motor means is expansible
	means to control supercharged	020	chamber type with movable
	flow and exhaust products		parts of motor and engine
601	With coordinated engine fuel		being interconnected
	control	621	Movable wall portions are
602	Having condition responsive	021	rigidly interconnected
	valve controlling engine	622	Expansible chamber of fluid
C02	exhaust flow	.	motor means receives exhaust
603	With coordinated fuel control		alternately from two or more
	means for engine		expansible chambers of engine
			means

623 624	Fluid motor is rotary type .Fluid motor means is a turbine	292	Valve at reactor outlet controlled
021	with output means mechanically interconnected with internal	293	Check valve feeds air to exhaust system
	combustion engine output	294	Reactor control correlated with
272	INTERNAL COMBUSTION ENGINE WITH		cyclic or external engine
	TREATMENT OR HANDLING OF		control
	EXHAUST GAS	205	
072		295	Having means for regenerating,
273	.Methods		replacing, or feeding liquid
274	Anti-pollution		or solid reagent or catalyst
275	.By electrolysis, electrical	296	Flow reversing structure
	<pre>discharge, electrical field, or vibration generator</pre>	297	Reactor plus a washer, sorber or mechanical separator
276	.Having means analyzing	298	With means cooling reactor or
	composition of exhaust gas		reactor feed
277	.Having sensor or indicator of	299	Using a catalyst
	malfunction, unsafeness, or	300	
	disarray of treater (e.g.,		Having a means for heating the catalyst
0.00	fusible link, etc.)	301	Reducing type catalyst
278	.Material from exhaust structure fed to engine intake	302	Catalyst in engine manifold or at exhaust port
279	Separated reactive constituent	303	Having heater, igniter, or fuel
	of exhaust fed to engine		supply for reactor
280	.Having auxiliary device	304	Oxidizer feed passage at engine
	mechanically driven by exhaust gas		exhaust valve, manifold or port
281	.Having exhaust gas collection	305	Distributed to plural
	and storage, or use as a	303	individual ports or valves
	pressure fluid source	206	
282	.By means producing a chemical	306	To port zone and downstream of
202			port
	reaction of a component of the	307	Pressurizing means feeds
000	exhaust gas		reactive air to reactor
283	With means handling crankcase,	308	Exhaust actuated air aspirator
284	carburetor, or gas tank vaporAutomatic or timed reactor	309	.Having retainer or flow director for exhaust gas condensate
	purge or heat-up in engine	310	.Treated by washing, or having
	starting operation		liquid contact structure
285	Engine fuel, air, or ignition	311	.By sorber or mechanical
	controlled by sensor of	311	-
	reactor condition	210	separator
286	Condition responsive control of	312	.Pulsed, timed, tuned or
200	heater, cooler, igniter, or		resonating exhaust
		313	Correlated exhausts from plural
000	fuel supply of reactor		cylinders
287	Condition responsive control of	314	Two-cycle engine
	reactor feed, pressure, or by-	315	.Pump draws exhaust gas from
	pass	313	engine
288	Exhaust gas diverted from	316	
	reactor or treating agent	310	Fluid jet or stream aspirates
	mixer		exhaust gas
289	Air feed to reactor modulated	317	.Exhaust and external fluid
	or diverted by control		mingling structure
200		318	External fluid is steam
290	Responsive to engine speed or	319	Exhaust aspirates external
001	intake manifold pressure		fluid
291	Of or by pressure in reactor		
	or of engine exhaust		

320	.Exhaust gas or exhaust system element heated, cooled, or used as a heat source	773 774 775	Having power output controlMultiple expansionIntroducing water or steam
321	Cooled manifold	776	Ignition or fuel injection
322	.Having vibration attenuating, or	770	after starting
322		777	-
	expansion and contraction relieving structure	777	Catalyst
222	_	778	Having particular starting
323	.Common receiver having inlets	779	Having particular safety
	from plural cylinder (i.e.,	780	Having fuel conversion (e.g.,
204	exhaust manifold)		reforming, etc.)
324	.Divider, collector, valve means,	781	Solid fuel
	or boundary layer device	782	Having bleed air to cool or
	controlling exhaust gas flow		heat motor or component
625	INTERNAL COMBUSTION ENGINE WITH		thereof (e.g., active
	STRUCTURE ROTATING OR STARTING		<pre>clearance control, etc.)</pre>
	IT BY PRESSURE FLUID	783	Combined with diverse nominal
626	.Having means for compressing,		process
	generating or storing pressure	784	.For nominal other than power
	fluid		plant output feature
627	Having condition responsive	785	Air bleed
	control of means	39.08	.With lubricators
628	Storage vessel charged by	39.091	.With safety device
	internal combustion engine	39.092	Debris anti-ingestion preventer
	acting as a pump	39.093	Ice preventer or de-icer
629	Pressure fluid motor	39.094	Fuel flusher or drainer
	convertible to pressure fluid	39.1	Excess pressure relief
	pump	39.11	Flame screen
630	.Having manual selector of engine	39.12	
	valve settings or of fluid	39.12	
	flow branches	39.13	.Automatic starting and stopping of combustion products
631	Including means selecting		generator
	direction of engine rotation	786	.Combined with starting feature
632	ONE SHOT EXPLOSION ACTUATED	787	Separate device or motive fluid
	EXPANSIBLE CHAMBER TYPE MOTOR	707	source
633	.Having means for feeding fluid	788	Starter motor mechanically
	fuel	700	coupled to power plant
634	.Having plural charge holding	789	Solid propellant charge
	means	109	initiates starting (e.g.,
635	.Having mechanical means securing		cartridge starter, etc.)
	working member in fired	790	Having condition responsive
	position	790	fuel control
636	.Having latch, rupture or safety	39.15	
	means resisting movement of		.Multiple fluid-operated motors
	working member or firing means	791	Re-expansion
	from unfired position	792	Multi-spool turbocompressor
637	.Having orifice or conduit	39.162	Counter - rotatable
	restricting flow of combustion	39.163	Selectively connectable
	products from combustion zone	39.17	With treatment between stages
	to motor chamber	39.181	Different fluids
638	.Having shock absorbing, damping	39.182	Steam and combustion products
	or slow down means for working	39.183	Air and combustion products
	member	39.19	.Different fluids
39.01	COMBUSTION PRODUCTS USED AS	39.23	.With variable oxidizer control
	MOTIVE FLUID	793	.Combined with regulation of
772	.Process		power output feature

39.21	<pre>Plural generators, selectively operable</pre>	39.49	.With air injection by fuel or steam jet
39.22	Varying cycle frequency	39.5	.With exhaust treatment
	relative to prime mover speed	39.511	Regenerator
39.24	Automatic	39.512	Rotary heat exchanger
39.25	Motive fluid to prime mover	39.52	Exhaust gas recycling
39.26	Oxidizer, fuel and water or	39.53	.With addition of steam and/or
	steam		water
39.27	Oxidizer and fuel	39.54	Added in prime mover
39.281	Fuel	39.55	Added in combustion products
39.282	Torque sensor		generator
794	Oxidizer	39.56	Mixed in space above water
795	Bleed	39.57	Combustion products pass
39.3	Water or steam		through water
796	.Having mounting or supporting	39.58	Added in mixing nozzle or in
	structure		turbine nozzle
797	For motor	39.59	Added in separate mixing
798	Having ease of assembly or		chamber
	disassembly feature	39.6	.External-combustion engine type
799	.Having expansible connection	39.62	With plurality of combustion
800	Combustor or fuel system		products generator per
801	.Convertible or combined with		cylinder
	feature other than combustion	39.63	Continuous combustion
	products generator or motor	39.64	.Alternate cycle
802	Motor driven accessory	722	.Combustion products generator
803	Motor condition sensing feature	723	Having catalyst in combustion
39.34	.Rotating combustion products		zone
	generator and turbine	724	Plural with intercycling by
39.35	Continuous combustion type		pressure fluctuations
804	.Coaxial combustion products	725	Having noise reduction means
	generator and turbine	726	With means to pressurize
39.37	.Plural combustion products		oxidizer for combustion or
	generators in ring coaxial		other purposes
	with turbine	727	With oxidizer accumulator
39.38	Intermittent combustion type	728	Having oxidizer cooling means
39.39	Common rotary distributing	729	Reciprocating positive
	valve		displacement type
39.4	Common cam member	730	With liquid heat exchanger
39.41	.With exhaust pump for combustion	731	With combuston products
	products generator		accumulator
39.42	.With reversible turbine	732	Having initial fuel-rich
39.43	.With dual function turbine		combustion zone
39.44	.With closed pocket turbine	733	Separate fuel injectors for
39.45	.With gear, pressure exchanger,	F 2 4	plural zones
	or screw-type compressor	734	Having fuel supply system
39.461	.Using special fuel or oxidizer	735	Fuel injected into turbine
39.462	Monofuel type	736	Fuel preheated upstream of
39.463	Plural distinct fuels	727	injector
39.464	Solid, slurry, emulsive, or	737	Fuel and air premixed prior to
	suspensive type fuel	720	combustion
39.465	Gaseous fuel at standard	738	Premix tube within combustion
20 45	temperature and pressure	739	zone
39.47	Solid fuel containing oxidizer	137	With fuel supply manifold for
39.48	.With fluid pressure feeding of	740	separate injectors
	oxidizer, fuel or water	/ 🛨 U	With fuel injector

741	Fuel control valve integral	639	MOTOR ACTUATED BY ACCUMULATING
742	with injectorUnitary injector having		AND DUMPING LIQUID OR FLUENT MATERIAL
7 12	plural fuel flow paths	640	.Rocking member having opposite
743	Surface film injector		accumulating means
744	Rotary fuel injector	641.1	UTILIZING NATURAL HEAT
745	Slinger type	641.2	.Geothermal
746	Plural distinct injectors	641.3	With direct fluid contact
747	Injectors in distinct	641.4	With deep well turbopump
	radially spaced parallel flow	641.5	With fluid flashing
	combustion products generators arranged to combine discharges	641.6	.With natural temperature differential
748	With attendant coaxial air swirler	641.7	Ocean thermal energy conversion (OTEC)
749	Having bluff flame	641.8	.Solar
	stabilization means	641.9	With distillation
750	Having means to recycle	641.11	With elevated structure
	combustion products internally	641.12	Air is working fluid
	of combustion zone	641.13	With single state working
751	Having diffuser for air inlet	011.13	substance
752	Combustor liner	641.14	Gaseous
753	Ceramic	641.15	With solar concentration
754	Porous	516	MOTOR OPERATED BY EXPANSION AND/
755	Having means to direct flow	310	OR CONTRACTION OF A UNIT OF
	along inner surface of liner		MASS OF MOTIVATING MEDIUM
756	Air directed to flow along inner surface of liner dome	517	.Unit of mass is a gas which is
757			heated or cooled in one of a
757 750	In an axial direction		plurality of constantly
758	Air introduced within liner counter to flow of combustion		communicating expansible chambers and freely
	products		transferable therebetween
759	Air scoop extends into air	518	Having means to change
735	flowing outside liner	310	operational phase relationship
760	Air outside liner flows		of working member and
700	counter to combustion products		displacer
	flow within liner	519	Expansible chamber having
805	Having turbine		rotatable or oscillatory
806	And cooling		displacer
39.76	Intermittent combustion type	520	Having free floating displacer
39.77	Resonating		or transfer piston
39.78	Rotating, oscillating, or	521	Having means to increase or
	reciprocating		diminish quantity of motivating mass
39.79	With fluid actuated valve	522	Having means to control rate of
39.8	With pressure actuated valve	022	flow of mass between chambers
39.81	With fuel metering valve	523	Having electrical heating means
39.821	With ignition device	323	for mass
39.822	Catalytic type	524	Having means to control
39.823	Pyrotechnic squib or charge type		temperature of heating or
39.824	Hypergolic type	525	cooling chamber
39.825	Single shot liquid type	243	Motor having plural working members
39.826	Pilot or torch type	526	
39.827	Spark type	240	Motor having regenerator for mass
39.828	Incandescent type	527	.Mass is a solid
39.83	.Cooling of auxiliary components	J21	

528	Mass heated because of	656	Harring angillary structure for
320	resistance to flow of electric	030	.Having ancillary structure for starting
	current	657	.Having apparatus cleaning,
529	Mass is bimetallic	037	sealing, lubricating, purging,
530	.Mass is a liquid		standby, or protecting feature
530	-	658	Damage to heat receiving
	Liquid is vaporized	030	
508	FLUID WITHIN EXPANSIBLE CHAMBER		element prevented by automatic means maintaining minimum flow
EOO	HEATED OR COOLED	659	
509	.Special motive fluid	039	.Including heat, steam, or
510	.Air rarefied by combustion	660	compressed gas storage means
511	.Fluid mingling (e.g.,	000	.Having condition responsive control
F10	condensation)	661	
512	.Having means within the working	001	Of or by heat rejecting means
	chamber to effect the pressure	662	or its bypass
E10	of fluid therein	002	Involving feed from source
513	Electric heating means		means to separate motor stages
514	.Concurrent fluid supply and	663	or utilizing means
	vaporization	663	Of branched feed to, condition
515	.Having control means for heating		of, or heating means for
	or cooling means		motive fluid between motor
642	MOTIVE STEAM GENERATED FROM HOT	664	stages
	WATER CHARGE BY REDUCING	004	Of or by heat source material or element
- 40	PRESSURE ABOVE CHARGE	665	
643	MOTIVE FLUID ENERGIZED BY	005	And of or by boiler liquid level or feed
C 4 4 3	EXTERNALLY APPLIED HEAT	666	
644.1	.Heating motive fluid by nuclear	000	Of bypass of superheater or
- 4 -	energy	667	desuperheater
645	.Process of power production or	007	Of means controlling boiler or its feed
- 1 -	system operation	668	
646	Including start up, shut down,	000	.Power system physically related to vehicle structure
	cleaning, protective or	669	
6.45	maintenance procedure	670	.Motor mounted in or on boiler
647	Including operating at or above	670	.Power system involving change of state
C 4 0	critical pressure	671	
648	Including production of	6/1	Motive fluid comprises a material other than steam or
	withdrawable product or steam		
- 4.0	for external use	672	water
649	Including mixing or separating	6/2	Motor exhaust used in
	materials of different	672	combustion zone
	chemical compositions in a	673	One fluid absorbs or reacts
650	motive fluid flow path	C7.4	with another
650	Producing power by heating and	674	Air and steam supplied to
CE 1	cooling a single phase fluid	675	motor
651	Including vaporizing a motive	675	Gravity motor actuated by
650	fluid other than water	60.6	weight of condensed vapor
652	Of accommodating, fluctuating	676	Including plural distinct
650	or peak loads		boilers, heat supplies or
653	Including superheating,	677	external sources of vapor
C = 4	desuperheating, or reheating	677	Serially connected motor with
654	Including mingling motor		intermotor supply or
	exhaust steam with boiler feed	670	withdrawal of motive fluid
655	water	678	Withdrawn fluid heats boiler
655	.Noncommunicating heat		feed indirectly
	transferring motive fluid		
	system (e.g., cascade, etc.)		

679	Having motive fluid reheater between serially connected motors	547.2	By pressure responsive valve dividing flow between motor and an auxiliary load
680	Motive fluid bypassing upstream motor heats reheater	547.3	By manually operated valve dividing flow between motor
681	Motor exhaust mixes with combustion products of boiler heater	548	<pre>and an auxiliary loadFlow in recirculating circuit controlled</pre>
682	Single state motive fluid energized by indirect heat transfer	549	Master structure provides non- overlapping periods of pressurization of diverse
683	Motor exhaust fed into combustion device		pressure ranges in distinct pulsator circuits
684	Including interstage reheat means	550	Master driven by manual power control lever on power failure
325	PRESSURE FLUID SOURCE AND MOTOR		and having means adjusting
532	.Shock or resonant wave type of energy transmission		lever throw or master resistance responsive to
533	.Pulsator		failure of power fluid supply
534	Having signal, indicator or	551	Manual master and controller
551	recorder of apparatus condition		of motor driven master actuated by separate linkages
535	Responsive to leakage of pulse fluid	552	to a common operating leverMechanical feedback to manual
536	Plural correlated pulsators transmitting unlimited rotary input to unlimited rotary		control controls power fluid to establish position of working member of master
	output	553	With distinct piston or
537	Programmed, self-cycled or self-pulsed		diaphragm exposed to pulsator pressure imparting feel to
538	Including electrical control or actuation	554	manual controlHaving load deformable means
539	Cam drive of plural masters		between master working member
540	Including timer or time delay		and motor thrust means
	means the cycle		adjusting bias of manual control
541	Having means terminating cycle at parking or holding position	555	Master movement of master produces a pressure that
542	Pneumatic device having pulse air bleed or supply means	556	controls the power fluidPower fluid input controller
543	Self-operated pulse fluid purge or quantity adjustment structure		operated by piston or diaphragm acted on one side by pressure of a manual master
544	Continuously acting self- pulsing master with manually settable slave release or	557	and on the other by pressure of a power driven masterPressurized fluid from manual
	output control valve		master charges slave and
545	Having electricity or magnetically operated		controls power fluid to separate master
	structure	558	Fluid from the manual master
546	Pulsator synchronizes movement of plural outputs		fed to slave through a passage in the working member of the
547.1	With control of or by a		power master
	separate power fluid, etc.	559	Passage extends across the expansible chamber of the motor of the power master
			•

560	Power fluid also fed into a separate expansible chamber directly driving output means	577	Central externally driven piston drives surrounding piston means through a load
561	Pressure balancing free piston or diaphragm between parallel pulsators	578	responsive connectorUnitarily movable displacer delivers fluid from two
562	Master piston of one pulsator circuit drives master piston of a parallel circuit through		delivery chambers, one chamber being ineffective under high pressure delivery
	a resilient, fluid or lost motion connection	579	Slave of first master drives master of another slave
563	Expansible chamber of output pressurized directly by motive	580	Parallel masters driven by first pulsator
	fluid and indirectly by a master driven by the motive fluid	581	Plural structurally related master pistons, cylinders or pulsator circuits
564	Delivery pressure of master lower than pressure driving master	582	Having safety standby structure becoming operative upon apparatus malfunction
565	Master and diverse non-pulsator drive of output member or members	583	Pulse fluid vessel embracing output piston and fluid displacing element
566	<pre>Manual master and alternate nonmanual pressure fluid source feed output motor</pre>	584	Having separately and manually operated structure for charging, discharging
567	Including plural separately operable master actuators or master units driving a common	585	<pre>bleeding, or adjusting pulsator volumeHolder for reserve liquid feeds</pre>
	slave		master
568	Having distinct means for holding a pulsator element in set position	586	Having means to establish holding pressure in pulse liquid
569	Distinct externally operable valve sealing pulse fluid in slave	587	<pre>Pressure maintained through inlet or piston cylinder of master</pre>
570 571	Mechanical latch, brake or detentDouble-acting slave unit or	588	Master piston traps liquid on advance across a feed port in cylinder wall
	opposed slaves having a single output	589	Master piston or its actuator mechanically operates valve
572	Having pulse fluid pressure or quantity compensating or adjusting means	590	between holder and master cylinder
573	Self-acting phase balancing means acting at midpoint or	390	Condition responsive device limits return flow from biased slave
574	<pre>end of strokeAutomatic control of plural</pre>	591	Having valve, director, or restrictor in pulse fluid flow
	stage pressure generation or utilization	592	<pre>pathHaving, surge chamber, fluid</pre>
575	Automatic trapping of fluid back of delivery piston forms temporary pulsator driving piston during one stage		supply means, or means compensating for fluid expansion, contraction or leakage
576	Of separate movement of plural delivery pistons	593	Having fluid motor driving piston of master unit

594	Having cam, or lever system driving master	346	Plural movable guides, one having a one-way clutch to
326	.Utilizing a mixture, suspension,		frame
	semisolid or electro-	347	Having condition responsive or
	conductive liquid as motive		manually settable control
	fluid		means to regulate unit output
327	.Methods of operation	348	Distributes motive fluid
328	.Having a signal, indicator or		between plural units, stages
	inspection means		or quides
329	.Condition responsive control	349	Adjusts impeller or turbine
	means responsive to, or		axially
	compensating for, motive fluid	350	Variable face clearance
	compressibility, temperature	351	Controls scoop operation for
	variation or viscosity		removing liquid from rotating
	variation driven master		casing
330	.Coaxial impeller and turbine	352	Of means within an impulse,
	unit		reaction or energy transfer
331	Reversible turbine or turbine		flow path being adjustable to
	system		modify flow of motive fluid
332	Having pitch control or motive	353	Motive fluid guide vane
	fluid flow guide or reaction		transferable axially into or
	blade means		out of motive fluid flow path
333	Having means to brake or free	354	Pitch or orientation of flow
	flow guide means		directing guide or blade
334	Having means to remove or		controlled
	insert flow quide means from	355	Speed responsive
	or into motive fluid flow path	356	Motive fluid pressure
335	Having plural individually		responsive
	actuatable units	357	Of means adjusting the mass of
336	Having filtering, de-aerating,		level of motive fluid at the
	cleaning or bleeding structure		impeller energy transfer zone
337	Having heating or cooling means	358	Including continuously driven
338	Having shock, vibration or		auxiliary pump
	surge control structure	359	Exhaust valve
339	Having lubricating means	360	Motive fluid pressure
340	Plural turbines drive		responsive
310	relatively movable output	361	Having separate guide or
	members		reaction means in circuit
341	Having brake or clutch		including impeller and turbine
0 1 1	controlling movement of a flow	362	Rotatable guide or reaction
	guide located in the impeller-		means coaxial with the
242	turbine flow path	262	impeller
342	With means adjusting blade	363	Plural impeller-turbine units
	orientation or blade exposure in flow path	364	Impeller or turbine integral
343	Speed or fluid condition	265	with unit housing
343		365 366	Fluid deflecting means
	responsive brake or manually adjustable brake	366 367	Toroidal impeller and turbine
344	Braked casing	307	Having core or ring member at
344	One-way clutch between the	260	interface
313	movable guide, an impeller,	368	.Control by independently
	turbine or a second movable		operated punch card, tape, digital computer, counter,
	guide		
	5.240		template, or programmer cyclic control
			COLLET OT

369	.Cyclically operable	387	.Distinct structure metering and
	reciprocating or oscillating motor or output stroke device		dispensing a stroke length determining volume of motive
370	Pneumatic motor		fluid to the motor
371	Having means to store and	388	.Full range correspondence of
	release energy usable to		position of external
	energize motor work output		manipulator and motor
	means		positioned member effected by
372	Pneumatic counter-balance of		feedback linkage
	gravity load on motor (e.g.,	389	Positioned member is
	deep well pump rod, etc.)		displacement controller of
373	Progressive change of stroke		second motor pump
	length in successive strokes	390	Electrical feedback means
374	Correlated independently	391	Feedback linkage controls
3,1	movable output members		variable displacement pump
375	Correlated power input pumps	392	Feedback includes plural
373	and/or pressurized fluid		movable valve parts
	sources	393	.Manipulator for motive fluid
376	Motor control means having	373	control valve having load feel
370	timer or time delay means		or motor pressure feedback
377	Provides dwell or press period	394	.Having apparatus control by
311	at end of stroke	371	timer or delay means
378	Having purging, surge	395	.Control relative to
370	accommodating, or leaking	373	independently driven
	handling or replenishing		oscillator, speed standard or
	structure		pacer device
379	Having condition responsive	396	.Utilizing lubricant, starter
375	cycle abort means or means for	330	motor, cooling fluid, or fluid
	manual control of motor output		used for combustion in an
380	With means to shut down system		internal combustion engine
300	after a complete to and fro	397	Vacuum generated by internal
	cycle of the motor means		combustion engine intake
381	Having condition responsive		manifold powers motor
301	control of variable	398	.Utilizing natural energy or
	displacement pump		having a geographic feature
382	Cam or gear carried by stroke	399	.Unsafeness, unreadiness or
302	device varies displacement		disarray prevent manual change
	pump		or operative state
383	Automatic or cyclic means	400	.Selective or simultaneous power
	provided plural distinct motor		and manual energy inputs
	speeds in cycle	401	Fluid motor and directs manual
384	.Expansible chamber type		drive of output device
	volumetric responsive	402	Separate manual and motor
	measuring device in series		driven pumps supply motive
	with or driven by output motor		fluid to output motor
	operates the motor controller	403	.Apparatus having means
385	.Manual pump pressurizes fluid to		responsive to or ameliorating
	position output motor motive		the effects of breakage,
	fluid control valve		plugging, mechanical failure
386	Manual pump supplies motive		or power failure
	fluid to output motor when	404	Stand-by stored energy means
	power motive fluid pump is		activated responsive to
	inactive		malfunction or power failure
		405	Second motive fluid supply
			means takes load responsive to
			failure of first

406	Output means locked, positioned or released on failure of	425	Condition responsive means establishes number of motor
407	motive fluid supply means .Pneumatic motor with gas supply	406	sections driving a common output
400	or removal device	426	Speed of, pressure in, or
408	Convertible motor-pump device selectively charges and is driven by gas from storage		<pre>position of one output motor or motor section controls another</pre>
	vessel	427	With manual control or
409	Having automatic control		selection of motor, motor
410	Responsive to condition in gas		speed or motor load
	storage vessel	428	.Having condition responsive
411	Suction pressure on motor regulated		control in a system of separately operable power
412	Having pump device		input pumps, pump motors, pump
413	.With control means for structure		cylinders or pressure fluid
	storing work driving energy	400	sources
	(e.g., accumulator, etc.)	429	With externally operated
414	Energy of braking or of		multiway valve changing the relationships of the motive
415	reversed load on motor stored		fluid pressurizing or
415	Accumulator pressurized by gas		supplying means
416	<pre>pump or external gas supplyPlural accumulators</pre>	430	Pressure or volume responsive
417	Stroke device driven by		means shifts the relationship
11 /	successively operated energy	431	.Condition responsive control of
	input structure and stored		or by input to input pump
	energy structure		drive means
418	Control by sensor of	432	Pump drive means deactivated
	accumulator condition		responsive to position of
419	.Motor driven by motive fluid of	433	output stroke device
	system drives pump	433	.Having correlated or joint actuation of controller of
	pressurizing motive fluid of		input to motive fluid
400	system		pressurizer and of controller
420	.Having condition responsive control in a system of		of motive fluid floow
	distinct or separately	434	Interlinked pump drive
	operable outputs or output		controller and manipulator of
	drive units		stroke device
421	With plural pump or motive	435	.Having a mechanical clutch or
	fluid source relationships		brake device in the power train
	selected by multiway valve	436	Correlated control of device
422	Independently actuatable	430	and motive fluid flow
	outputs with condition		controller
	responsive means insuring	437	Selective fluid and mechanical
	sufficiency of feed of motive fluid		drive of output from input
423	Including means for controlling	438	Condition responsive selection
123	or for reversing input pump	439	Device acts on intermediate
	drive		reactive rotor to modify speed
424	Serially connected motors		ratio or direction
	controlled to establish	440	Condition or direction
	parallel operation or to by-	4.4.7	responsive device
	pass a motor means of the	441	Condition or direction
	series	442	responsive device
		774	Device holds output in adjusted position

443	.Servo-motor having externally operated control valve sets motor or pump displacement	464	Of motive fluid transfer between a reservoir and a recirculating path of a pump
444	Having auxiliary pump or external source of motive fluid supplying servo motor	465	<pre>motor loopHaving externally operable means for setting motor or</pre>
445	.Condition responsive control of pump or motor displacement		<pre>pump displacement or direction of rotation</pre>
446	Pump displacement varied responsive to position of	466	Of braking or holding valve in motor discharge line
447	<pre>motor or output deviceControl actuated by a servo- motor fed by a speed</pre>	467	Stroke cylinder open to exhaust responsive to position of output member
	indicating auxiliary pump	468	Of by-pass of motor, pump or
448	By means sensing rotational		flow control element
	speed of output motor	469	.Having means controlling or
449	By means sensing rotational speed of prime mover or pump		attenuating shock vibration, sticking or chattering
450	<pre>Choke in motor feed or discharge line establishes displacement control pressure (e.g., rate of flow responsive, etc.)</pre>	470	Externally operated multiway valve or interconnected control elements control motive fluid for a limited stroke to-and-fro device
451	Controlled by torque of motor	471	Having plural distinct or
	or motor discharge pressure		separately operable output
452	Pump displacement controlled by		means
	<pre>pump discharge or motor feed pressure</pre>	472	Flow to opposed expansible chambers having a common
453	.With means purging, cleaning or	473	output reversed
45.4	separating undesirables from motive fluid	4/3	.Pump means moves motive fluid from one chamber to an
454	Solids from liquid separator		opposite chamber of opposed expansible chambers having a
455	.Having leakage collecting structure		common output
456	.Having distinct cooling or	474	Valve or restriction controls
430	lubricating structure		gravity or spring return of
457	.Collapsible joined device having		output
	fluid trapping valve in joint	475	With means compensating for
458	.Having assembly or repair structure		charge leakage or volume difference between discharging
459	.Condition responsive control of motive fluid flow	476	and receiving chambersReversible delivery from pump
460	Holding or braking valve in motor exhaust line controlled	477	means .Ram driven by fluid pumped from reservoir
461	by pressure in motorfeed line	478	Having means pressurizing,
401	Discharge from contracting cylinder of double-acting motor controlled		vacuumizing or venting reservoir
462	With externally operable	479	Having selective or variable
102	multiwasy valve means		pump displacement or pump
	directing flow to a stroke		drive leverage
	device	480	Telescopic ram
463	Sensor of external condition controls valve	481	Having fluid trapping means with a manual release or by- pass holding ram

482	Release valve and pump actuated by a common handle	504	Having flexible strand working member motion transmitting
483	.Having selecting means distributing motive fluid	505	<pre>meansHaving relatively movable</pre>
	between plural motors or		working members
	cylinders rotatating a common output shaft	506	Working member pivotally supported
484	.Having plural energy outputs	507	Having one-way clutch power
485	<pre>(e.g., plural motors, etc.)Unit having coaxial rotary</pre>		<pre>transmission means, e.g., ratchet, etc.</pre>
	output shafts and pump means in a common housing (e.g.,	685	MOTOR HAVING EXHAUST FLUID TREATING OR HANDLING MEANS
	automobile differential, etc.)	686	.Having condition responsive
486	.Having plural energy input means, pumps or diverse pump		control of exhaust structure or by exhaust condition
	outlets	687	.Motor-exhaust assembly with
487	.Input pump and rotary output motor system having		stress relieving or absorbing structure
	displacement varying type of	688	.Water mingled with exhaust steam
488	direction or speed selectorIncluding auxiliary system feed	689	.Exhaust fluid mingled with non- exhaust fluid
	pump	690	.Motor and indirect heat
489	Having valve means controlling		exchanger
400	flow between pump and motor	691	Boiler feed water heated by
490	Both motor and pump have		exhaust
491	displacement adjustment means	692	Having condensate pump
491	Having common or intercontrolled adjuster	693	Plural heat exchangers
400	actuating means	694	.Including exhaust flow directing or dividing device
492	Motor swash plate and pump swash plate intercontrolled	695	Device directs exhaust of air
493	.Valve means reverses flow from	696	motor into atmosphereDevice is draft structure of
	pump to reversible rotary	090	hydraulic motor
494	<pre>motor .Including by-pass or restrictor</pre>	697	Turbine discharge directed to flow line
	controlling flow circuit	698	SYSTEM HAVING PLURAL MOTORS OR
495	MOTOR HAVING A BUOYANT WORKING MEMBER	0,50	HAVING DIVERSE TYPES OF ENERGY INPUT
496	.With means to vary buoyancy of	699	.Spring type motor and internal
40=	working member		combustion engine motor
497	.Working member actuated by the rise and fall of a surface of a body of fluid	700	.Motors intercontrolled responsive to angular speed differential of rotatable
498	Having tide responsive working		output shafts
400	member positioning means	701	Hydraulic or pneumatic
499	Having means responsive to lateral impulse of fluid		intercontrol system
500	Having articulated buoyant	702	Electrical intercontrol system
	members	703	<pre>.Control including pacer, oscillator, punch card,</pre>
501	Motor is free floating unit	- 6.	template or tape
502	Having fluid flow or wave controlling, confining or	704	.Control including clock, retarder or programmer
F02	directing means	705	.Signal, indicator or inspection
503	In which the control means is variable		means

900

901

EXCESS AIR TO INTERNAL COMBUSTION

ENGINE TO ASSIST EXHAUST

EXHAUST TREATMENT SPECIAL TO

ROTARY INTERNAL COMBUSTION

TREATMENT

ENGINES

706	.Having condition responsive control	902	ROTARY REACTOR, SEPARATOR OR TREATER OF EXHAUST OF AN		
707	Of branched flow of motive		INTERNAL COMBUSTION ENGINE		
707	fluid through serially	903	CLOSURES OPERATORS		
	connected motors	904	PROPELLER OR AIR PLANE SYSTEM		
708	Of or by motor cooling,	905	WINDING AND REELING		
700	ventilation, or brake system	906	ENGINE SPEED RESPONSIVE THROTTLE		
709	Of or by disconnect or load	900	CONTROL SYSTEM		
	release means to output means	907	WORKING MEMBER POSITIONED AGAINST		
	or between motors		COUNTERFORCE BY CONSTANTLY		
710	Intercontrol of internal		APPLIED MOTIVE FLUID		
	combustion engines responsive	908	WASHING MACHINE SYSTEM		
	to relative fuel or manifold	909	REACTION MOTOR OR COMPONENT		
	conditions		COMPOSED OF SPECIFIC MATERIAL		
711	First motor load share adjusted	910	FREE PISTON		
	relative to the load share of	911	FLUID MOTOR SYSTEM INCORPORATING		
	a second motor driving a		ELECTRICAL SYSTEM		
	common load, responsive to a	912	COOLING MEANS		
	condition of the second motor	913	COLLECTION OF REGGIO PATENTS		
710	or of the load	914	EXPLOSIVE		
712	.Engine apparatus or system	915	COLLECTION OF GODDARD PATENTS		
	actuatable selectively or simultaneously by internal	916	UNITARY CONSTRUCTION		
	combustion of fuel and by	917	SOLID FUEL RAMJET USING		
	expansion of motive fluid		PULVERIZED FUEL		
713	.Plural motors having brake means				
, _ 5	for motor or output means				
714	.Plural motors having supply or				
	control of cooling,	FOREIG	N ART COLLECTIONS		
	lubricating, or scavenging				
	fluid	FOR 000	CLASS-RELATED FOREIGN DOCUMENTS		
715	.Plural motors, connected for	3 £			
	serial flow of motive fluid	Any foreign patents or non-patent litera-			
716	.System of plural motors having a		ture from subclasses that have been reclassified have been transferred		
	common output structure		y to FOR Collections listed below.		
717	And another output		These Collections contain ONLY foreign		
718	Having disconnect means between		patents or non-patent literature. The par-		
	a motor and the output	entheti	cal references in the Collection		
719	.Interrelated or group control	titles	refer to the abolished subclasses		
	operating means for plural	from wh	ich these Collections were derived.		
	motors or outputs				
720	.Unitary support for plural				
E01	motors				
721	MISCELLANEOUS		REACTION MOTOR (E.G., MOTIVE		
			FLUID GENERATOR AND REACTION		
			NOZZLE, ETC.) (60/200.1)		
anc		FOR 100	O .Including afterburner (60/261)		
CROSS-	REFERENCE ART COLLECTIONS	FOR 103	1 .Air supplied by ram effect (60/		
0.00			270.1)		

FOR 102 .Motive fluid outlet means (60/

FOR 104 .. Regulation of power output (60/

FOR 105 ...Multiple expansion (60/39.04)

271)

FOR 103 .Processes (60/39.02)

39.03)

- FOR 106 ..Addition of steam and/or water (60/39.05)
- FOR 107 ... Ignition and/or fuel injection (60/39.06)
- FOR 108 .With nonmotor output (60/39.07)
- FOR 109 .With starting device (60/39.141)
- FOR 110 ...Separate starting device or motive fluid source (60/ 39.142)
- FOR 111 ... Re-expansion (60/39.161)
- FOR 112 .With regulation of power output (60/39.2)

COMBUSTION PRODUCTS USED AS MOTIVE FLUID (60/39.01)

- .With variable oxidizer control (60/39.23)
- ..Automatic (60/39.24)
- FOR 113 ...Oxidizer (60/39.29)
- FOR 114 .With mounting or supporting structure (60/39.31)
- FOR 115 .With expansible connections (60/ 39.32)
- FOR 116 .Convertible and combined (60/ 39.33)
- FOR 117 .Coaxial combustion products generator and combined (60/39.36)
- FOR 118 ..With turbine (60/39.75)